



1. Standard integral 7.62mm stem is shown, non-standard lengths and/or 5.56mm diameter may be specified.
2. Standard telescope includes adjustable & illuminated reticle, variable diopter setting, nitrogen fill valve.

UNLESS OTHERWISE NOTED  
 .X = ± .020    .XX = ± .010  
 .XXX = ± .005    .XXXX = ± .0005  
 FRACTIONS ± 1/64"  
 ANGLES ± 1°  
 CONCENTRICITY TIR=.001  
 PERPENDICULARITY TIR=.001  
 PARALLELISM TIR=.001  
 BREAK ALL SHARP EDGES  
 ALL DIMENSIONS IN INCHES

**NOTICE**  
 THIS DRAWING AND THE SUBJECT MATTER  
 DISCLOSED HEREIN ARE PROPRIETARY  
 ITEMS TO WHICH GRAFLEX, INC. RETAINS  
 THE EXCLUSIVE RIGHT OF DISSEMINATION,  
 REPRODUCTION, MANUFACTURE AND SALE.  
 THE DRAWING, PRINT OR DOCUMENT IS  
 SUBMITTED IN CONFIDENCE FOR CONSID-  
 ERATION BY THE RECIPIENT ALONE UNLESS  
 PERMISSION FOR FURTHER DISCLOSURE IS  
 EXPRESSLY GRANTED IN WRITING.  
 Date: 06-17-2014

<b>GRAFLEX</b> INCORPORATED 18855 Assembly Loop Suite 100 - Jupiter, FL 33478 (661) 691-5959 fax (561) 691-5983			
TITLE <b>Standard 8X Telescope</b>			
SIZE <b>C</b>	CAGE CODE <b>00ZS7</b>	DWG NO	REV
SCALE	STEPHEN TEKLINSKI		SHEET